



CARMEL

MADE FROM AVIATION-GRADE ALUMINUM AND HIGH-STRENGTH IMPACT-RESISTANT POLYMER, THE CARMEL RIFLE HAS PROVEN ITSELF OVER AND OVER AGAIN WORLDWIDE. THIS RIFLE IS DESIGNED TO MEET THE NEEDS OF END USERS WHO REQUIRE OUTSTANDING PERFORMANCE IN ANY KIND OF ENVIRONMENTAL CONDITIONS. FEATURING A ROTATING BOLT SYSTEM AND AN ENHANCED FIRING PIN SAFETY MECHANISM, THIS RIFLE IS DESIGNED WITH MAXIMUM USER SAFETY IN MIND. THE CARMEL IS EASY TO CUSTOMIZE FOR THE USER'S NEEDS AS A FULLY TOOLLESS AMBIDEXTROUS PLATFORM AND IS EQUIPPED WITH A FULL-LENGTH MIL STANDARD 1913 PICATINNY TOP RAIL AND MLOK ON ALL SIDES TO MAKE USE OF ANY AVAILABLE SIGHTS, DEVICES, OR ACCESSORIES, WHICH REDUCES THE OVERALL COST OF THE SYSTEM THROUGH 100% INTERCHANGEABILITY. AT ITS HEART, THE CARMEL IS DESIGNED WITH ERGONOMICS IN MIND AND BUILT TO LAST A LIFETIME.

SPECS

- ▶ COLOR: BLACK
- ▶ CALIBER: 5.56 NATO
- ▶ ACTION: SEMI-AUTOMATIC
- ▶ OPERATING SYSTEM: SHORT-STROKE PISTON ROTATING LOCKING BOLT WITH 2 POSITION GAS REGULATOR
- ▶ MAGAZINE TYPE: MAGPUL PMAG GEN M3 WITH WINDOW
- ▶ MAGAZINE CAPACITY: 30 ROUND
- ▶ BARREL TYPE: FREE-FLOATING, CHROME LINED, COLD HAMMER FORGED
- ▶ BARREL LENGTH: 16"
- ▶ OVERALL LENGTH: 26 3/4" STOCK FOLDED, 33 3/4" STOCK COLLAPSED, 37 1/4" STOCK EXTENDED
- ▶ WEIGHT: 8 LBS 2 OZ WITHOUT MAGAZINE
- ▶ RIFLING: 1:7" TWIST, 6 RH GROOVES (5.56 NATO)



*ATTACHMENTS NOT INCLUDED

FEATURES

- ▶ OPTIMIZED ERGONOMIC DESIGN
- ▶ SHORT-STROKE GAS PISTON
- ▶ COMPLETELY AMBIDEXTROUS AND CAN BE CONVERTED EASILY IN THE FIELD WITHOUT TOOLS
- ▶ 2-POSITION GAS REGULATOR - (REGULAR, SUPPRESSOR)
- ▶ COLD HAMMER-FORGED, CHROME-LINED, FREE-FLOATING BARREL FOR ENHANCED ACCURACY & PROLONGED LIFE CYCLE
- ▶ MLOK ACCESSORY RAILS AT THE 3, 6, AND 9 O'CLOCK POSITIONS
- ▶ THE WEAPON CAN BE FIRED WITH A FOLDED STOCK
- ▶ ENLARGED TRIGGER GUARD FOR EASIER ACCESS FOR GLOVE USE
- ▶ DESIGNED FOR MINIMUM OPERATOR AND ARMORER LEVEL MAINTENANCE
- ▶ CORROSION-RESISTANT METAL
- ▶ HIGH STRENGTH IMPACT RESISTANT POLYMER BODY
- ▶ USES ANY NATO MIL-STD 5.56 STEEL, ALUMINUM, OR POLYMER MAGAZINES
- ▶ 3 POINTS OF SLING ATTACHMENTS - QD OR CORD

